THE RANGE OF ENGINE CONTROLLERS from POWER EQUIPMENT

Specifically designed to suit Yanmar engines in Australian and New Zealand conditions.



The range of Engine Controllers represents a significant upgrade in technology, functionality and physical appearance. The sturdy enclosed case on the PE–MANUAL and PE-AUTO has a weather seal to protect against dust and water. The PE-NANO, with its open style enclosure, is rated at IP65 for longer protection.

FEATURES AND BENEFITS

- (VARIES BY MODEL)
- Keyless Start & Stop
- Oil Pressure & Coolant Temp Protection
- Battery Monitoring
- 2 Wire Start/Stop
- Twin Float Start/Stop
- Pump Pressure Monitoring & Start Stop
- Engine Coolant and Temp Protection
- Loss of Prime
- Tachometer/Hourmeter
- 99 hour Run Timer (only PE-Manual & PE-Auto)
- 7 day Repeatable Start/Stop Timer
- Individual Daily Start/Stop (Mon-Sun)
- Fault Indicator & Error Log

ADDITIONAL OPTIONS

- Remote E-Stop
- Remote 3G Monitoring and Control Telemetry Package
- Pump Pressure
- Low Coolant Level (optional if capability fitted to engine)

Power ≥quipment^{*} For more information contact Power Equipment Pty Ltd:





| | | L SERIES Electric start only | TF SERIES Electric start only | TNV SERIES |
|-------------|--|---------------------------------|---------------------------------------|---------------------------------------|
| - NANO | Features | | | |
| | Keyless Start/Stop | ✓ | ✓ | ✓ |
| | Tachometer | ✓ | ✓ | ✓ |
| | Hourmeter | ✓ | ✓ | ✓ |
| | Low Oil Pressure Protection | ✓ | ✓ | ✓ |
| | Engine Coolant Temp Protection | N/A | ✓ | ✓ |
| | Battery Monitoring | ✓ | ✓ | ✓ |
| | Water in Fuel | N/A | N/A | N/A |
| | Fault Indicator | ✓ | ✓ | ✓ |
| | Fault Error Log | ✓ | ✓ | ✓ |
| | Optional Extras | | | |
| | Remote Stop (E-stop) | ✓ | ✓ | ✓ |
| | Low Coolant Level | N/A | N/A | ✓ |
| PE - MANUAL | Features | | | |
| | Keyless Start/Stop | ✓ | ✓ | ✓ |
| | Tachometer | ✓ | ✓ | ✓ |
| | Hourmeter | ✓ | ✓ | ✓ |
| | Low Oil Pressure Protection | ✓ | ✓ | ✓ |
| | Engine Coolant Temp Protection | N/A | ✓ | ✓ |
| | Battery Monitoring | ✓ | V | ✓ |
| | Water in Fuel | N/A | N/A | N/A |
| | 99hr Run Timer | ✓ | V | ✓ |
| | Fault Indicator | V | V | V |
| | Fault Error Log | V | V | V |
| | 2 Wire Start/Stop | V | · · · · · · · · · · · · · · · · · · · | · · · · · · · · · · · · · · · · · · · |
| | Twin Float Start/Stop | V | V | |
| | Pump Pressure Monitoring & Start/Stop | | · · · · · · · · · · · · · · · · · · · | · · · · · |
| | Optional Extras | • | • | • |
| | Remote Stop (E-stop) | V | ✓ | ✓ |
| | Low Coolant Level | N/A | N/A | |
| PE - AUTO | Features | N/A | N/A | • |
| | Keyless Start & Stop | V | ✓ | ✓ |
| | Tachometer | | · · · · · · · · · · · · · · · · · · · | |
| | Hourmeter | | | |
| | Low Oil Pressure Protection | | · · · · · · · · · · · · · · · · · · · | |
| | Engine Coolant Temp Protection | N/A | | |
| | Battery Monitoring | ₩A | · · · · · · · · · · · · · · · · · · · | V |
| | Water in Fuel | N/A | N/A | N/A |
| | 99hr Run Timer | ₩A ✓ | IN/A | ₩A ✓ |
| | Fault Indicator | V | V | V |
| | | V | V | · · · |
| | Fault Error Log | | | |
| | 2 Wire Start/Stop | V | V | V |
| | Twin Float Start/Stop | V | V | V |
| | PumpPpressure Monitoring & Start/Stop | V | | · · |
| | Loss of Prime | | | <u> </u> |
| | 7 Day Repeatable Start/Stop Timer | ✓ | | |
| | Individual Daily Start/Stop timer (Mon-Sun) | ✓ | ✓ | ✓ |
| | Optional Extras | | | |
| | Remote Stop (E-stop) | V | ✓ | / |
| | Remote 3G Monitoring and Control Telemetry Package | ✓ | | ✓ |
| | Low Coolant Level | N/A | N/A | ✓ |

OPTIONAL EXTRAS



PE PRESSURE

.

20 Bar (300PSI) Pump Pressure Transducer with 8 pin connector



web: phon

E-STOP SWITCH Remote Stop (E-Stop) complete with 2M harness and 4 pin connector

Power Equipment reserves the right to change technical specifications without notice.



For more information contact Power Equipment Pty Ltd: email

| : | info@powerequipment.com.au |
|----|----------------------------|
| | www.powerequipment.com.au |
| e: | 1800 069 469 |